




NOTES:

1. MATERIAL : 300 SERIES STAINLESS
2. 24 IN. GRAB HANDLE MAY HAVE ONE INTERRUPTED SECTION OF KNURLING APPROXIMATELY 1.00 WIDE LOCATED IN CENTER OF PATTERN. 30 IN. GRAB HANDLE MAY HAVE TWO EQUALLY SPACED INTERRUPTED SECTIONS IN KNURLING, APPROXIMATELY 1.00 WIDE
3. RECOMMENDED FASTENER : 3/8-16 UNC ALLEN HEAD BOLT, SAE GRADE 5 MINIMUM
4. PART IS SYMMETRICAL ABOUT CENTERLINES SHOWN
5. DIMENSIONS ARE FOR REFERENCE ONLY

PART NUMBER	LENGTH "X"	LENGTH "Y"	LENGTH "Z"
GHKN09SSPL-18	18 IN.	17 IN.	7.6 IN.
GHKN09SSPL-24	24 IN.	23 IN.	13.6 IN.
GHKN09SSPL-30	30 IN.	29 IN.	19.6 IN.



DESCRIPTION:	1-1/8" DIA KNURLED GRAB RAIL	Weight NA
Part Number:	GHKN09SSPL-XX	REV -
PROPRIETARY NOTICE: THIS DRAWING IS EXCLUSIVELY THE PROPERTY OF HANSEN INTERNATIONAL INC. AND SHALL NOT BE COPIED OR PASSED ON TO A THIRD PARTY WITHOUT OUR PRIOR WRITTEN APPROVAL. WE WILL RETAIN ALL RIGHTS FOR PATENT ISSUE OR REGISTRATION OF DESIGN. ©2018 Hansen International, Inc.		